Ethernet Switches

	Type	Channels	Management	Dimensions	Front Connector	Consumption typ.	Software
RS1	Wall-mount or DIN-rail	8 x 100Base-T	Managed, PoE (1,2)	200 x 130 x 70 mm	M12	24 W (incl. 15 W PoE)	Management firmware
RS2	Wall-mount or DIN-rail	8 x 100Base-T	Unmanaged, PoE (1,2)	200 x 130 x 70 mm	M12	24 W (incl. 15 W PoE)	No
RS3	Wall-mount or DIN-rail	8 x 100Base-T	Managed	200 x 130 x 70 mm	M12	5 W	Management firmware
RS4	Wall-mount or DIN-rail	8 x 100Base-T	Unmanaged	200 x 130 x 70 mm	M12	5 W	No
SF1	19" or stand-alone	8 x 100Base-T	Unmanaged, PoE (1,2)	19", 18 HP	RJ45	24 W (incl. 15 W PoE)	No
SF2	19" or stand-alone	8 x 100Base-T	Managed, PoE (1,2)	19", 18 HP	RJ45	24 W (incl. 15 W PoE)	Management firmware
SF3	19" or stand-alone	8 x 100Base-T	Managed, PoE (1,2)	19", 22 HP	M12 (D-Sub on request)	24 W (incl. 15 W PoE)	Management firmware
SF4	19" or stand-alone	8 x 100Base-T	Unmanaged, PoE (1,2)	19", 22 HP	M12 (D-Sub on request)	24 W (incl. 15 W PoE)	No
F301	3U CompactPCI 32-bit/33-MHz	8+1 x 100Base-T	Unmanaged	3U, 8 HP	RJ45 or D-Sub	3 W	No
F302	3U CompactPCI 32-bit/33-MHz	8+1 x 100Base-T	Managed	12 HP (with RJ45) or 16 HP (with M12)	RJ45 or M12	5 W	Management firmware
G301	3U CompactPCI Serial	4+1 x 1000Base-T	Unmanaged	3U, 4 HP	RJ45 or M12	28 W (incl. PoE)	No
G302	3U CompactPCI Serial	16 x 1000Base-T	Managed	3U, 4 HP	RJ45 or M12	15 W	Management firmware
G303	3U CompactPCI Serial	16 x 1000Base-T	Unmanaged	3U, 4 HP	RJ45 or M12	15 W	No