

CT12 – Supported CPUs

CPU Supported Functions Matrix

Functions	F11S	F19P	F21P**	F22P**	F50P	F75P*
Ethernet Port 1	-	✓	✓	✓	-	✓
Ethernet Port 2	-	-	-	-	-	✓
USB 2.0 Port 1	-	✓	✓	✓	✓	✓
USB 2.0 Port 2	-	✓	✓	✓	✓	✓
USB 2.0 Port 3	-	✓	✓	✓	✓	✓
USB 2.0 Port 4	-	✓	✓	✓	✓	✓
SATA Port 1	✓	✓	✓	✓	✓	-
SATA Port 2	-	✓	✓	✓	✓	-
SATA Port 3	-	✓	✓	✓	-	-
SATA Port 4	-	✓	✓	✓	-	✓
PCI Express Port 1	-	✓	✓	✓	-	✓
PCI Express Port 2	-	✓	✓	✓	-	-
PCI Express Port 3	-	✓	✓	✓	-	-
PCI Express Port 4	-	✓	✓	✓	-	-

* Note: For the F75P some signals are assigned differently, connecting to these functions on the CT12 (marked with a "-" in the above table) is not recommended.

** As an option, the F21P and the F22P offer the possibility of routing one Ethernet port from the front panel to the back, which is only available on a specific board version.

